

CHAINLUBE 240



Silicone free conveyor lubrication

Description: Fully synthetic lubricant base, silicone free, reduces carbon build-up and extends cleaning intervals.

Application: Suitable for lubrication of hot conveyor chains in drying oven and tenter frames at chain temperature of up to 240°C. The lubricant can be used in paint oven operations because there is no silicone to contaminate components prior to painting and cause fish-eye imperfections in the paint surface.

- Benefits:**
- *Keep chains clean and free of carbon build-up.*
 - *Minimizes chain and sprocket wear.*
 - *Reduces lubricant consumption.*
 - *Lower energy consumption.*
 - *Outstanding high-temperature performance.*
 - *Improves operational safety.*
 - *Less smoke.*

Health and Safety: Base on available toxicological information, this product produces no adverse effects on health when properly handled and used. No special precautions are suggested beyond attention to good personal hygiene, including laundering oil-soaked clothing and washing skin-contact areas with soap and water.

Typical Characteristics

<i>Product Number</i>	240
<i>Specific Gravity @ 15/15°C</i>	0.910
<i>Flash Point, °C</i>	240.6
<i>Viscosity at 40°C, cSt</i>	210
<i>Viscosity at 100°C, cSt</i>	22
<i>Viscosity Index</i>	126
<i>Copper Corrosion, ASTM D 130</i>	3B

PP Systems Co., Ltd.

*Registered address: 49 Soi LuanjueaAnusorn2, Sukhumvit 70/3 Road, Bangna, Bangkok, Thailand 10260
Tel. +66 (0) 2399 4930, +66 (0) 2745 4900 Fax. +66 (0) 2745 2098, +66 (0) 2398 7113
E-mail: pp@ppss.co.th, satit@ppss.co.th Website: <http://www.ppss.co.th>*