

主機性能表 Pump specifications

馬達噴霧機 Powe	r sprayer	with motor								
型 號 Model		M 2005	M 2510	M 2511	M 4520	M 4521	M 5030	M 5031	M 8050	M 8051 -
馬 力 Motor	(hp)	1/2	1	1	2	2	3	3	5	5
電 力 Power	(V/ph.)	110/1 220/1	110/1 220/1	220/3 380/3	110/1 220/1	220/3 380/3	220/1	220/3 380/3	220/1	220/3 380/3
尺寸 Measure LxWxH(cm)		44x 33x 33	58x 36x 46	58x 36x 46	90x 36x 50	90x 36x 50	90x 36x 50	105x40x53	105x40x53	115x52x62
重量Weight	(kg)	25	35	32	47	45	65	60	110	95
噴 霧 機 Spraye	r				-1.					
型 號 Model		P20	P25		P45		P50		P80	
尺寸 Measure LxWxH(cm)		27x 48x 25	37 x 26.5 x 23		43 x 30 x 34		43 x 32 x 45		50 x 41 x 63	
重 量 Weight (kg)		5	11		16		28		52	
迴轉速 R.P.M.		600-1500	400-600		500-700		400-600		400-600	
噴霧量 Volume (L/min)		6-14	8-12		20-28		30-45		50-85	
馬 力 Motor (hp)		1/2	1/2-1		1-2		2-3		3-5	
引 擎 Enginel (ps)		1.5-3	3-5		5-8		5-8		5-8	
定向噴嘴 (每迴路數量)	I 20	150	200		350		750		1400	
	I 30	125	150		300		550		1100	
One loop Nozzle set	I 40	90	110		210		400		800	
	1 50	70	90		180		340		600	
	I 60	30	40		80		150		300	
360 [°] 迴轉噴頭 (每迴路數量)	R600	15	20		40		75		150	
	R3000	3	4		8		15		30	
One loop	R201	4	5		10		18		35	
Nozzle set	R202	2	3		5		10		15	

控制箱 Control panel

編號 Item No	C 0101	C 0105	C 0110	C 0201	C 0205	C 0210	C 0301	C 0305	C 0310	C 0401	C 0405	C 0410	
迴路 Loop	1	5	10	1	5	10	1	5	10	1	5	10	
馬力 Motor (hp)	1~3			3~5			13			3~5			
控制 Control	溫控加計時(Thermograph+Timer)						溫,濕控加計時(Thermograph/Humidistat+Timer)						
電力 Power (v/ph.)	220/380v 50Hz/60Hz												